GA FineFloor FibreBoard

Insulating panels of natural wood fibre, designed to eliminate uneven floors

Technical Data

On the level

As well as insulation, FibreBoard provides a level subfloor for the final floor covering, offering stable support and helping your floor last longer by smoothing out the most uneven areas.

Keep out the cold

The exceptional thermal insulation of FibreBoard is perfect for use on very cold subfloors such as cellars, to make your room feel so much cosier and comfortable.

Easy to fit

Made from traditional natural wood fibre, you'll find FibreBoard really easy to line up, cut and fit - saving you a great deal of time and effort wherever you're installing it.

Properties	4mm (Thin)	5.5mm (Classic)	7mm (Levelling)
Dimensions [mm]	590 x 850	590 x 850	590 x 856
Qty pcs by pack	25	20	19
Qty m² in a pack	12.53m ²	10.03m ²	9.60m ²
Qty pack on pallet	20	20	18
Qty m² in a pallet	250.6m ²	200.6m ²	172.8m ²
Weight of pallet	250kg	275kg	300kg
Acoustic Installation	18dB	18dB	18dB
Thermal Conductivity	0.050W/mK	0.050W/mK	0.050W/mK
Static Bending Strength	min. 1.6 Mpa	min. 1.6 Mpa	min. 1.6 Mpa
Density	260kg/m ³ <u>+</u> 10%	260kg/m ³ <u>+</u> 10%	260kg/m ³ <u>+</u> 10%
Humidity	up to 9%	up to 9%	up to 9%
Swelling in thickness after 2hours	up to 8%	up to 8%	up to 8%
Levels base irregularity Fine Floor 4mm	up to 2mm	up to 2mm	up to 2mm
Levels base irregularity Fine Floor 5.5mm	up to 3mm	up to 3mm	up to 3mm
Levels base irregularity for Fine Floor 7mm	up to 4mm	up to 4mm	up to 4mm


QA Flooring Solutions Ltd

Block H, Pickerings Road, Widnes, Cheshire WA8 8XW Tel: 0151 495 3434 Fax: 0151 420 9062 Email: sales@qaflooringsolutions.com www.qaflooringsolutions.com The information given above may vary and is partly based on information from our suppliers. It represents the prevailing level of expertise and is not binding in a legal sense. The compliance of legal requirements lies within the customers own responsibility.

Simply Better

Medium Traffic

Wood



Best for Cushioning Moisture Protection Sound Reduction Level Floors Compression Recovery Underfloor Heating Hard Wearing Heat Insulation Commercial Use*

*Suitable for hotels and public buildings

Available in

Code	QAU-FFF-01
Size	590mm x 850m (12.53m ²)
Thickness	4mm
Code	QAU-FFF-02
Size	590mm x 850m (10.03m ²)
Thickness	5.5mm
Code	QAU-FFF-03
Size	590mm x 850m (7.02m ²)
Thickness	5.5mm
Code	QAU-FFF-04
Size	590mm x 856m (9.6m ²)
Thickness	7mm