

Solid Natural Vertical 96mm

For residential use

Key Features

- 100% renewable and sustainable Moso Bamboo monitored plantations
- Extremely hard and stable with excellent indentation resistance
- Easy and quick to install
- Comparable stability to engineered wood boards

Construction & Profile

- Three layer 15mm thick solid bamboo flooring glued in horizontal slats to create a wide grain look



960 x 96 x 15mm (2.21m² per pack)

Finish

- 6 layers of satin German lacquer, inc UV protection. Coatings are water based, solvent-free and comply with European (E1) standards for off-gassing

* Residential structural warranty

Performance	Standard	Result
Flammability resistance	ASTM E648	Critical radiant panel test Class 3 rating untreated
Hardness	ASTM D1037 (Janka)	1393lbf (6.2kN)
Formaldehyde emissions	EN 717-1: 2004	0.080mg/m ³ (E1)
Slip resistance	EN 1339:2003	R9
Moisture content	-	8-10%
Density	EN 323: 1993	1.159/cm ³



Strand Woven Bamboo - 15.8

Jatoba - 10.5

Merbau - 8.6

Jairrah - 8.5

Maple - 6.4

Solid Bamboo - 6.2

White Oak - 6.0

Beech - 5.8

Janka Hardness Scale

The higher the number, the harder the surface. All measurements are shown in kilonewtons (kN)

