## Solid Carbonised Vertical 96mm

BAMBOO FLOORING COMPANY COM


For residential use

## **Key Features**

- 100% renewable and sustainable Moso Bamboo monitored plantations
- Extremely hard and stable with excellent indentation resistance
- Easy and quick to install
- Comparable stability to engineered wood boards

## **Construction & Profile**

- Three layer 15mm thick solid bamboo flooring glued in horizontal slats to create a wide grain look



 $960 \times 96 \times 15 \text{mm} (2.21 \text{m}^2 \text{ per pack})$ 

## **Finish**

- 6 layers of satin German lacquer, inc UV protection. Coatings are water based, solvent-free and comply with European (E1) standards for off-gassing

\* Residential structural warranty

Performance	Standard	Result
Flammability resistance	ASTM E648	Critical radiant panel test Class 3 rating untreated
Hardness	ASTM D1037 (Janka)	1393lbf (6.2kN)
Formaldehyde emissions	EN 717-1: 2004	0.080mg/m3 (E1)
Slip resistance	-	
Moisture content	-	8-10%
Density	EN 323: 1993	1.159/cm3

25
YEAR
WARRANTY\*

Strand Woven Bamboo Jatoba - 10.5 Merbau - 8.6 Jarrah - 8.5 Maple - 6.4 Solid Bamboo - 6.2 White Oak - 6.0

Janka Hardness Scale

The higher the number, the harder the surface. All measurements are shown in kilonewtons (kN)





