## Solid Carbonised Strand Woven 142mm

V.BAMBOOFLOORINGCOMPANY,COM

For commercial & residential use

## **Key Features**

- 100% renewable and sustainable Moso Bamboo monitored plantations
- Bamboo sourced from managed forests
- Extremely hard and stable with excellent indentation resistance
- Easy and quick to install Uniclic® locking system
- Compatible with wet under floor heating systems

## **Construction & Profile**

- Strand woven tongue and groove with micro bevelled edge.



1850 x 142 x 14mm (1.58m<sup>2</sup> per pack)

## **Finish**

- 6 layers of satin German lacquer, inc UV protection. Coatings are water based, solvent-free and comply with European (E1) standards for off-gassing

\* Residential structural warranty Commercial structural 10 year warranty

Performance	Standard	Result
Flammability resistance	EN 13501-1:2007	Class Cf1-s1
Hardness	ASTM D1037 (Janka)	3562lbf (15.8kN)
Formaldehyde emissions	EN 717-1: 2004	0.080mg/m3 (E1)
Slip resistance	-	
Moisture content	-	8-10%
Density	EN 323: 1993	84-0 N/mm2

Jatoba - 10.5 Merbau - 8.6 Jarrah - 8.5 Maple - 6.4

White Oak - 6.0

Janka Hardness

The higher the number, the harder the surface. All measurements are shown in kilonewtons (kN)





