

Engineered Carbonised Strand Woven 190mm

For commercial & residential use

EST. 2004


bambooflooringcompany.com

Key Features

- 100% renewable and sustainable Moso Bamboo monitored plantations
- FSC 100% - Bamboo sourced from managed forests
- Extremely hard and stable with excellent indentation resistance
- Easy and quick to install Uniclic® locking system
- Compatible with wet under floor heating systems

Construction & Profile

- Engineered board with a plywood base and 4mm strand woven wear layer. Micro bevel with Uniclic® system on all 4 sides.



1850 x 190 x 14mm (2.81m² per pack)

Finish


- 7 layers of Matt Bona Naturale lacquer. Coatings are water based, solvent-free and comply with European (E1) standards for off-gassing

* Residential structural warranty
Commercial structural 10 year warranty

Performance	Standard	Result
Flammability resistance	EN 13501-1:2007	Class Cf1-s1
Hardness	ASTM D1037 (Janka)	3562lbf (15.8kN)
Formaldehyde emissions	EN 717-1: 2004	0.080mg/m3 (E1)
Slip resistance	EN 1339:2003	R10
Moisture content	-	8-10%
Density	EN 323: 1993	84-0 N/mm2



Strand Woven Bamboo - 15.8



Janka Hardness Scale

The higher the number, the harder the surface. All measurements are shown in kilonewtons (kN)

