

# Engineered Carbonised Strand Woven 190mm

WWW.BAMBOOFLOORINGCOMPANY.COM


For commercial & residential use

### **Key Features**

- 100% renewable and sustainable Moso Bamboo monitored plantations
- Bamboo sourced from managed forests
- Extremely hard and stable with excellent indentation resistance
- Easy and quick to install Uniclic® locking system
- Compatible with wet under floor heating systems

#### **Construction & Profile**

- Engineered board with a plywood base and 4mm strand woven wear layer. Micro bevel with Uniclic® system on all 4 sides.



 $1850 \times 190 \times 14$ mm (2.81m<sup>2</sup> per pack)

#### **Finish**

- 7 layers of Matt Bona Naturale lacquer. Coatings are water based, solvent-free and comply with European (E1) standards for off-gassing

\* Residential structural warranty Commercial structural 10 year warranty

Performance	Standard	Result
Flammability resistance	EN 13501-1:2007	Class Cf1-s1
Hardness	ASTM D1037 (Janka)	3562lbf (15.8kN)
Formaldehyde emissions	EN 717-1: 2004	0.080mg/m3 (E1)
Slip resistance	BS 7976-2	R10
Moisture content	-	8-10%
Density	EN 323: 1993	84-0 N/mm2

25 YEAR WARRANTY\*



Jatoba - 10.5
Merbau - 8.6
Jarrah - 8.5
Maple - 6.4
Solid Bamboo - 6.2
White Oak - 6.0

## Janka Hardness Scale

The higher the number, the harder the surface. All measurements are shown in kilonewtons (kN)



Strand Woven Bamboo -



