

# Solid Carbonised Strand Woven 125mm

For commercial & residential use

## Key Features

- 100% renewable and sustainable Moso Bamboo monitored plantations
- Bamboo sourced from managed forests
- Extremely hard and stable with excellent indentation resistance
- Easy and quick to install Uniclic® locking system
- Compatible with wet under floor heating systems

## Construction & Profile

- Strand woven bamboo with a micro bevel and Uniclic® system on all 4 sides.



915 x 125 x 10mm (2.29m<sup>2</sup> per pack)

## Finish


- 7 layers of Matt Bona Naturale lacquer. Coatings are water based, solvent-free and comply with European (E1) standards for off-gassing

\* Residential structural warranty  
Commercial structural 10 year warranty

Performance	Standard	Result
Flammability resistance	EN 13501-1:2007	Class Cf1-s1
Hardness	ASTM D1037 (Janka)	3562lbf (15.8kN)
Formaldehyde emissions	EN 717-1: 2004	0.080mg/m3 (E1)
Slip resistance	BS 7976-2	R10
Moisture content	-	8-10%
Density	EN 323: 1993	84-0 N/mm2



Strand Woven Bamboo - 15.8



## Janka Hardness Scale

The higher the number, the harder the surface. All measurements are shown in kilonewtons (kN)

