

Solid **Rustic Carbonised Strand Woven 135mm**

WWW.BAMBOOFLOORINGCOMPANY.COM

For commercial & residential use

Key Features

- 100% renewable and sustainable Moso Bamboo monitored plantations
- Bamboo sourced from managed forests
- Extremely hard and stable with excellent indentation resistance
- Easy and quick to install Uniclic® locking system
- Compatible with wet under floor heating systems

Construction & Profile

- Strand woven bamboo with a micro bevel and Uniclic® system on all 4 sides.



 $1850 \times 135 \times 14$ mm (1.5m² per pack)

Finish

- 7 layers of Matt Bona Naturale lacquer. Coatings are water based, solvent-free and comply with European (E1) standards for off-gassing

* Residential structural warranty Commercial structural 10 year warranty

Performance	Standard	Result
Flammability resistance	EN 13501-1:2007	Class Cf1-s1
Hardness	ASTM D1037 (Janka)	3562lbf (15.8kN)
Formaldehyde emissions	EN 717-1: 2004	0.080mg/m3 (E1)
Slip resistance	EN 1339:2003	R10
Moisture content	-	8-10%
Density	EN 323: 1993	84-0 N/mm2

Strand Woven Bamboo - 15.8

Jatoba - 10.5

Merbau - 8.6

Jarah - 8.5

Maple - 6.4

Solid Bamboo - 6.2

White Oak - 6.0

Beech - 5.8

The higher the number, the harder the surface. All measurements are shown in kilonewtons (kN)







The Bamboo Flooring Company Unit 5, Euston Street, Freemens Common, Leicester LE2 7ST Tel: 0116 2741050 Fax: 0116 2741046 Email: mail@bambooflooringcompany.com