

Solid Pebble Strand Woven 125mm


For commercial & residential use

Key Features

- 100% renewable and sustainable Moso Bamboo monitored plantations
- Bamboo sourced from managed forests
- Extremely hard and stable with excellent indentation resistance
- Easy and quick to install Uniclic® locking system
- Compatible with wet under floor heating systems

Construction & Profile

- Strand woven bamboo with a micro bevel and Uniclic® system on all 4 sides.



915 x 125 x 10mm (2.29m² per pack)


Finish

- 7 layers of Matt Bona Naturale lacquer. Coatings are water based, solvent-free and comply with European (E1) standards for off-gassing

* Residential structural warranty
Commercial structural 10 year warranty

| Performance | Standard | Result |
|-------------------------|--------------------|------------------|
| Flammability resistance | EN 13501-1:2007 | Class Cf1-s1 |
| Hardness | ASTM D1037 (Janka) | 3562lbf (15.8kN) |
| Formaldehyde emissions | EN 717-1: 2004 | 0.080mg/m3 (E1) |
| Slip resistance | EN 1339:2003 | R10 |
| Moisture content | - | 8-10% |
| Density | EN 323: 1993 | 84-0 N/mm2 |

25
YEAR
WARRANTY*



Janka Hardness Scale

The higher the number, the harder the surface. All measurements are shown in kilonewtons (kN)

